

TETRA UHF

UHF Elevated Antenna

04/04/2016 v2



BSU

2dBi Omnidirectional

Mast Mount


Temporary or Permanent

Quick Assembly

The BSU type antenna is a 2dBi gain discreet ruggedized product and is suitable for temporary field use or permanent installation. The antenna has a black plated brass centre hub, which is mounted on a nylon stub mast and is supplied with mounting hardware. The hub has a N socket terminal which allows use of different types and diameter coaxial cable, depending on cable length required. The plastic coated $\frac{1}{4}$ wave radiating element is fitted to the centre of the hub and three helical elements provide the ground plane.

Typical applications for this antenna are: for use on mobile pump up mast, fixed radio terminal (FRT) and mobile/fixed repeater installations.


Technical Drawing




TETRA UHF

UHF Elevated Antenna

Typical H-Plane (390MHz)



Typical VSWR*



* VSWR measured with 5m (17') of CS23 cable.

Part No.				
	BSU-S1	BSU-S2	BSU-TET	BSU-S4
Electrical Data				
Frequency Range (MHz)	380-400	410-430	380-430	450-470
Operational Band	S1	S2	TET	S4
Peak Gain: Isotropic	2dBi	2dBi	2dBi	2dBi
Compared to ¼ wave	0dB	0dB	0dB	0dB
Typical VSWR	<1.5:1	≤ 1.5:1	≤ 1.5:1	≤ 1.5:1
Polarisation	Vertical	Vertical	Vertical	Vertical
Pattern	Omnidirectional	Omnidirectional	Omnidirectional	Omnidirectional
Impedance	50Ω	50Ω	50Ω	50Ω
Max Input Power (W)	100	100	100	100
Mechanical Data				
Dimensions (mm)	Total Length	358 (1.2')	344 (1.1')	351 (1.1')
	'L1' length	198 (7.8")	184 (7.2")	191 (7.5")
	'L2' length	68 (2.7")	64 (2.5")	65 (2.6")
Operating Temp (°C)	-30° / +80°C (-22° / +176°F)	-30° / +80°C (-22° / +176°F)	-30° / +80°C (-22° / +176°F)	-30° / +80°C (-22° / +176°F)
Colour	Black	Black	Black	Black
Materials	TPE, Nylon,Black Chrome Plated Brass.	TPE, Nylon,Black Chrome Plated Brass.	TPE, Nylon,Black Chrome Plated Brass.	TPE, Nylon,Black Chrome Plated Brass.
Termination Data				
Termination	N socket	N socket	N socket	N socket



Panorama Antennas Ltd
Frogmore, London, SW18 1HF, United Kingdom

T: +44 (0)20 8877 4444
F: +44 (0)20 8877 4477

E: sales@panorama-antennas.com
www.panorama-antennas.com

Waiver: The data given above is indicative of the performance of the product/s under particular conditions and does not imply a guarantee of performance. These specifications are subject to change without notice.

Copyright © Panorama Antennas Ltd. All rights reserved.